# MSA Bell FlameKing® Jacket

Technical Data Sheet



Multi norm Linesman Jacket with latest technology fabric, lined for extra warmth offering very high protection against Electric Arc, Flash Flame and Anti Static. Durable, comfortable and excellent quality personal protective equipment (PPE) with GORE-TEX PYRAD® Technology particularly for those working in potentially hazardous environments and in tough weather conditions. Maximizes comfort, waterproofness protection and breathability with light weight.









\* available to order optionally

## **DESCRIPTION**

- Ergonomic design
- Zip front fastening with storm flap
- Inner soft storm collar
- Two outer pockets with storm flaps
- Key loop in front edge of both pockets
- 1 x zipped vertical pocket on left front
- 1 x inside pocket on lining, lower left front with Velcro fastening
- Fully lined for comfort and warmth
- Double layer contrast cloth shoulder panels, with closed cell foam shoulder pads sandwiched between

- No seam along natural shoulder line, shaped shoulder panel instead
- Ergonomic curved sleeve with contrast inner elbow panels
- · Underarm gussets
- Adjustable external Velcro cuffs
- · Soft FR inner storm cuff
- Hanging loop
- Available with a large size hood which fits over safety helmet (DH01) or a small size hood (DH02). (Hoods are sold separately)

## **TECHNICAL SPECIFICATION**

- 99.4% Polyester/ 0.6% Carbon with GORE-TEX PYRAD® Technology
- 215 g/m2
- 150 g/m2 Kermel viscose lining (FR)
- GORE-TEX® Rainchamber tested (EN ISO 14360)
- Standard 100 by OEKO-TEX® Class II Certified

SIZE GUIDE				
WEARER'S CHEST		WEARER'S WAIST		GARMENT
INCHES	СМ	INCHES	СМ	SIZE
34 - 36	84 - 92	26 - 28	68 - 72	SMALL
38 - 40	96 - 100	30 - 32	76 - 80	MEDIUM
42 - 44	104 - 112	34 - 36	84 - 88	LARGE
46 - 48	116 - 120	36 - 38	92 - 96	X-LARGE
50 - 52	124 - 132	40 - 42	100 - 104	XX-LARGE
54 - 56	136 - 140	46 - 48	108 - 112	XXX-LARGE

#### Product code

- FK252PGE\_YEL
- 2 FK252PGE ORA

#### PRODUCT INFORMATION

COLOUR:

HiVis Yellow or HiVis Orange with contrast panels

**SIZES:** S to 3XL

PRODUCT CARE:



























#### **STANDARDS**

EN ISO 20471 Class 3 EN 343 Class 43. EN 1149 - 5 EN ISO 11612 A1 B2 C1 F1 EN ISO 11611 A1 Class 2 EN 61482 Class 2 ELIM 39 Cal<sup>2</sup> & ATPV 40 Cal<sup>2</sup> EN 14360 FK252PGE\_ORA additionally certified for RIS-3279-TOM









### **APPLICATION AREAS**











Chemical Generation