



K60B series Portable Single Gas Detector



K60B single gas detector with BLUETOOTH function

K60B series gas detector is a full featured device that has unequaled cost of ownership! The detector is warranted for one year and maintenance free with replaceable battery.

Key Features:

- 1) Equipped with import CITY, Alphasense, Dynament, SGX, Honeywell sensors
- 2) Light weight and small size design (less than 120g), easy to operate
- 3) Bright, red flashing visible alarm
- 4) 90dB audible vibration alarm
- 5) Excellent built-in vibration alert for use in areas of high ambient noise
- 6) Strong, protective, concussion-proof design of IP67 protection able working in harsh environments
- 7) 3.7V rechargeable lithium battery, continuously work for 10+hours
- 8) 2+2 digits LCD real time display gas concentration
- 9) CERTIFICATIONS: CE, CMC, Ex, MA (Certification for COAL MINING PRODUCTS IN CHINA)
- 10) K60B series with Network wireless (Optional): Bluetooth, 4G, NB, connect to the mobile APP and upload data.

Technical Specifications:

Item: Model NO.:	portable single gas detector K60
Sensors:	UK sensors (brand CITY, Alphasense, Dynament etc.), US (brand Honeywell), Japan and Germany sensors, ensuring high stability & sensitivity
Sensor service life:	2 years
Operating voltage:	3V lithium battery
Display:	LCD display
Alarm buzzer:	90db
Alarm mode:	acousto optic alarm
Ambient temperature:	- 20 ° C ~ + 50 ° C
Relative humidity:	15~90%RH(non condensation)
Material:	ABS, slip silicone
Detecting method:	diffusion
Dimension(mm):	109×56×38mm
Explosion-proof grade:	ExdII CT3
Weight :	120g
Package:	carton
Pcs/ctn:	1pc/ctn
Ctn size:	150x105x47mm
Payment terms:	T/T
Warranty:	1 year

Mark: other customized gas types are also available.

Gas Types	Detection range	Response Time	Resolution	Alarm Values
O ₂	0-25%vol/30%vol	T90≤20s	0.1%vol	18.0%vol/23.0%vol
LEL	0-100%LEL	T90≤30s	1%LEL	25.0%LEL/50.0%LEL
CO	0-1000 ppm/2000ppm	T90≤30s	1 ppm	50ppm/100ppm
H ₂ S	0-200 ppm	T90≤30s	0.1 ppm	10ppm/20ppm
SO ₂	0-200ppm	T90≤30s	0.1 ppm	2 ppm /10 ppm
Cl ₂	0-20 ppm	T90≤30s	0.1 ppm	1 ppm /10 ppm
NH ₃	0-100ppm/2000ppm	T90≤50s	1 ppm	25 ppm /50 ppm
NO ₂	0-200ppm	T90≤25s	0.1 ppm	3 ppm /10 ppm
NO	0-1000 ppm	T90≤50s	1 ppm	25 ppm /50 ppm
O ₃	0-1ppm/10ppm	T90≤30s	0.1ppm	0.3ppm/5ppm
PH ₃	0-10ppm	T90≤60s	0.1ppm	0.3ppm/5ppm
H ₂	0-2000ppm/4%vol	T90≤50s	1 ppm	50ppm /100ppm
HF	0-10ppm	T90≤50s	0.1ppm	3ppm /10ppm
HCL	0-30ppm/200ppm	T90≤50s	0.1 ppm	5ppm /10ppm
HCN	0-50ppm	T90≤200s	0.1ppm	10 ppm /20 ppm

IP GRADE: IP67 testing



K60B Single gas detector



Sensorer


