

Tactical Communication Units

MM50-TAC2 Remote Speaker Microphone & Control Box for 2 radios



The MM50-TAC2 DUAL RSM & Control Box

The MM50-TAC2 is a state-of-the-art high-tech Remote Speaker Microphone. The MM50-TAC2 can work independently as a RSM, but even better with the IE2-TAC, where situational awareness and hearing protection comes into play.

The MM50-TAC2 is made for users needing to communicate via 2 radios. The PTT buttons are split to handle each individual radio and when using the IE2-TAC headset the receiving audio is split up.

Main Radio = Right Ear Secondary Radio = Left ear

INDUSTRIES



OPTIONS



Use with IE2-TAC Headset

Technical data

Microphone	Omni directional	Environmental specifications	
Sensitivity	- 42dB +/- 3dB	Operating temperature	-25° C to +60° C
Speaker	36mm Ø Dynamic	Storage temperature	-40° C to +85° C
Output power	1W Max 1,5W	Mechanical specifications	
Output level	91dB +/- 3dB	Cable flex life	50,000 cycles
Frequency range	580Hz ~ 5KHz	Cable pull strength	Axial 13 kgs
Front PTT	Main radio	PTT switch life	100,000 cycles
Side PTT	Secondary radio	Protection rating	IP67