

ROSTAING

LIBÉREZ VOTRE POTENTIEL

TECHNICAL SHEET

RESCUEFLUOBC-SC

FIRE-FIGHTER LINE

WORKING GLOVE

- Traffic accident rescue
- Vehicle extrication
- Rescue and clean-up
- Handling with risks of cut
- Hose reeling

Abrasion protection level
on the back: 3

ISO
13997

Palm 32,1N
Back 28,2 N



AET N°0075/011/162/03/20/0725 EXT01/04/20 (CTC LYON)

STANDARDS (DETAILS ON WEB SITE)
www.rostaing.com/normes-securite

SIZES

6 7 8 9 10 11 12

COMPOSITION

Palm Polyurethane coating, cow split leather reinforcement + foamback protection
Back Shock absorbing thermoplastic reinforcements
Glove HPPE/mineral fibres weave
Total length 25 cm

CARE



PACKAGING

Bag of 1 pair / Box of 50 pairs

Type B products

 **Standardised shock protection**

 **Maximum cut resistance**
Technological weave

 **Grip in oily and humid environments**



Heat resistance

Thermal insulation:
250°C for 10 seconds
minimum



Very good puncture resistance

On the reinforced areas

Protective foam

D30²



ROSTAING 17 Av. Charles de Gaulle - 01800 Villieu - FRANCE
Tél +33(0)474 460 710 - Fax +33(0)474 613 443

ROSTAING.COM

Maximum cut protection

Impact protection

Comfort with foam padding in the palm → shock absorption

Enhanced durability with the addition of a leather reinforcement on the palm